





CAD FILE:

MODEL NO.	KNOB(G/VG)
T2-232032B-G	(2~15)mm



SCHEMATIC (NON-SHORTING)



CMTDDZ

SPECIFICATIONS

Rating	0.5A 50V DC
CIRCUIT	2P3T
Timing	NON-SHORTING
Travel	2.0mm
Contact Resistance	< 100 mΩ
Operating Force	250gf ± 100gf
Operating Life	10,000 cycles

NO.	PARTS	MATERIALS	Q'TY	FINISH	TOLERANCE UNLESS SPECIFIED WITHIN 1.5mm : ±0.1mm OVER 1.5mm : ±0.2mm		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DONGGUAN TIANDU ELECTRONICS CO.,LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF DONGGUAN TIANDU ELECTRONICS CO., LTD		DESCRIPTIONS OF REVISION		APPD.
8											
7	STEEL BALL	STEEL	1	NATURAL							
6	SPRING	STEEL WIRE	1	NATURAL							
5	CONTACT CLIP	PBS STRIP	2	Ag PLATED							
4	TERMINAL	BRASS STRIP	6	Ag PLATED							
3	BASE	PHENOLIC RESIN	1	NATURAL							
2	FRAME	STEEL STRIP	1	BLACK							
1	KNOB	POM	1	BLACK							
					TITLE : VERTICAL SLIDE SWITCH			UNIT : mm		DRWG NO.: CMTDDZ-T2-232032B-00	
					MODEL: T2-232032B-G			SCALE: 3:1		DWN. ERIC 2013-6-17	
					CMTDDZ 东莞市田都电子有限公司 DONGGUAN TIANDU ELECTRONICS CO.,LTD.			CHK'D MAIKO		2013-6-17	
								APPD. Coco		2013-6-17	