





RoHS Compliant



RECOMMENDED P.C.B LAYOUT

规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)
2. 端子保持力: Terminal Retention
1.0kgf(MIN)
3. 寿命: Durability
1500 CYCLES MIN

- T10-2F634D-X X X X X X X X
- B=盐雾24H C=盐雾48H
 - 包装方式PACK:
2: 盒装 3: 管装 4: 载带
 - 端子电镀SPRING PLATING:
0: 镀金GF 5:5u" 6:15u" 8:30u"
 - 端子材质SPRING CONTACT:
C:黄铜 P:磷铜
 - 外壳电镀SHELL PLATING:
N:镀锌 T:镀雾锡
 - 外壳材质SHELL:
S:不锈钢 C:黄铜 A:冷轧钢板
 - 塑胶颜色HOUSING COLOUR:
W:白色 B:黑色 L:蓝色 Y:黄色 G:绿色
 - 塑胶材质HOUSING:
0:PBT 3:LCP 6:PA-6T 9:PA-9T

CMTDDZ 东莞市田都科技有限公司 Dongguan Tiandu Technology Co., Ltd TEL:0769-85384807 FAX:0769-85384842		图号 (DWG NO)		单位 (UNIT): MM
		版本 (REV)	A/0	比例 (SCALE) 1:1
品名 (ITEM NO)		USB A/F短体10.0 插板4脚直边 6.3H	日期 (DATE)	2015.06.09
料号 (PART NO)		T10-2F634D-XXXXXXX	设计 (DESIGN)	ERIC
模号 (MODEL NO)		N/A	审核 (CHECKED)	~
			核准 (APPROVED)	
			未注公差 TOLERANCE UNSPECIFIED I X ±0.30 I XX ±0.20 I XXX ±0.10 I* ±0.5 I** ±0.2	